

02 Split Series U-Match Cassette

R 22



PARAMETROS

		UCCA - 12HR	UCCA - 18HR	UCCA - 24HR	UCCA - 36HRT	UCCA - 48HRT	
CARACTERÍSTICAS DE LA UNIDAD	Capacidad enfriamiento	(Btu / H)	12.000	18.000	24.000	36.000	48.000
		W	3.517	5.000	7.000	10.000	14.000
	Capacidad Calefacción	(Btu / H)	14.000	19.800	27.300	37.600	53.000
		W	4.103	5.800	8.000	11.000	15.500
	Alimentación eléctrica	V / P / Hz	220 / 1 / 50	220 / 1 / 50	220 / 1 / 50	380 / 3 / 50	380 / 3 / 50
	Power input enfriamiento	Kw	1,6	2,0	2,6	3,6	5,8
	Power input calefacción	Kw	1,5	1,9	2,5	3,1	6,2
	Current Input enfriamiento	A	7,5	9	11,9	6,7	10,5
Current Input calefacción	A	6,8	8,7	11,4	5,7	11,3	
Carga de refrigerante	Kg	1,1	1,5	2	3,2	3,8	
UNIDAD INTERIOR	Caudal de aire	(m3 / h)	600	680	1.180	1.600	1.700
	Nivel de Ruido	dB (A)	47	47	47	48	48
	Dimensiones de Contorno (LxAxH)	cm	59 x 59 x 24	60 x 60 x 23	84 x 84 x 24	84 x 84 x 32	84 x 84 x 32
	Dimensiones de Empaque (LxAxH)	cm	69 x 85 x 30	68 x 85 x 31	96 x 96 x 31	96 x 96 x 40	96 x 96 x 40
	Peso Neto	Kg	20	20	30	38	38
PANEL	Dimensiones de Contorno (LxAxH)	cm	65 x 65 x 50	65 x 65 x 50	96 x 96 x 60	96 x 96 x 60	96 x 96 x 60
	Dimensiones de Empaque (LxAxH)	cm	67 x 73 x 102	7 x 73 x 6102	104 x 103 x 115	104 x 103 x 115	104 x 103 x 115
UNIDAD EXTERIOR	Nivel de Ruido	dB (A)	56	56	59	60	63
	Dimensiones de Contorno (LxAxH)	cm	26 x 76 x 53	32 x 85 x 54	41 x 102 x 70	41 x 102 x 84	41 x 103 x 125
	Dimensiones de Empaque (LxAxH)	cm	36 x 88 x 59	36 x 88 x 59	45 x 110 x 76	45 x 111 x 99	45 x 111 x 139
	Peso Neto	Kg	32	48	59	60	63
TUBERIA	Tubería de Líquido	pulgadas	1 / 4	1 / 4	3 / 8	1 / 2	1 / 2
	Tubería de Gas	pulgadas	1 / 2	1 / 2	5 / 8	3 / 4	3 / 4
	Long.Max.Tuberías	m	20	20	30	50	50
	Max.dif. de Altura entre UI y UE	m	15	15	15	30	30

- Equipo de largo alcance
- Filtro lavable de larga duración
- Bajo nivel de ruido

