

03

Split Series U-Match Cassette

Ecológico

R 410a



P A R A M E T R O S

UCCA - 12HRE

UCCA - 18HRE

UCCA - 24HRE

UCCA - 36HRE

UCCA - 48HRE

CARACTERÍSTICAS
DE LA UNIDAD

Capacidad enfriamiento	(Btu / H)	12.000	18.000	24.000	36.000	48.000
	W	3.517	5.000	7.000	10.000	14.000
Capacidad Calefacción	(Btu / H)	14.000	19.800	27.300	37.600	53.000
	W	4.103	5.800	8.000	11.000	15.500
Alimentación eléctrica	V / P / Hz	220 / 1 / 50	220 / 1 / 50	220 / 1 / 50	380 / 3 / 50	380 / 3 / 50
Power input enfriamiento	Kw	1,6	2,0	2,6	3,6	5,8
Power input calefacción	Kw	1,6	1,9	2,5	3,1	6,2
Current Input enfriamiento	A	7,3	9	11,9	6,7	10,5
Current Input calefacción	A	7,3	8,7	11,4	5,7	11,3
Carga de refrigerante	Kg	1,0	1,5	2	3,2	3,8

UNIDAD
INTERIOR

Caudal de aire	(m3 / h)	600	680	1.180	1.600	1.700
Nivel de Ruido	dB (A)	47	47	47	48	53
Dimensiones de Contorno (LxAxH)	cm	59 x 59 x 24	60 x 60 x 23	84 x 84 x 24	84 x 84 x 32	84 x 84 x 32
Dimensiones de Empaque (LxAxH)	cm	69 x 85 x 30	68 x 85 x 31	96 x 96 x 31	96 x 96 x 40	96 x 96 x 40
Peso Neto	Kg	20	20	30	38	38

PANEL

Dimensiones de Contorno (LxAxH)	cm	65 x 65 x 50	65 x 65 x 50	96 x 96 x 60	96 x 96 x 60	96 x 96 x 60
Dimensiones de Empaque (LxAxH)	cm	73 x 67 x 102	73 x 67 x 102	103 x 104 x 115	103 x 104 x 115	103 x 104 x 115

UNIDAD
EXTERIOR

Nivel de Ruido	dB (A)	56	56	59	60	63
Dimensiones de Contorno (LxAxH)	cm	76 x 26 x 53	85 x 32 x 54	102 x 41 x 70	102 x 41 x 84	103 x 41 x 125
Dimensiones de Empaque (LxAxH)	cm	88 x 36 x 59	88 x 36 x 59	110 x 45 x 76	111 x 45 x 99	111 x 45 x 139
Peso Neto	Kg	32	48	59	128	128

TUBERÍA

Tubería de Líquido	pulgadas	1 / 4	1 / 4	3 / 8	1 / 2	1 / 2
Tubería de Gas	pulgadas	1 / 2	1 / 2	5 / 8	3 / 4	3 / 4
Long.Max.Tuberías	m	20	20	30	50	50
Max.dif. de Altura entre UI y UE	m	15	15	15	30	30



- Equipo de largo alcance
- Filtro lavable de larga duración
- Bajo nivel de ruido

