

04 Split Series U-Match Ducto

R 22



PARAMETROS

UCDU - 18HR UCDU - 24HR UCDU - 36HRT UCDU - 48HRT UCDU - 60HRT

CARACTERÍSTICAS DE LA UNIDAD			UCDU - 18HR	UCDU - 24HR	UCDU - 36HRT	UCDU - 48HRT	UCDU - 60HRT
Capacidad Enfriamiento	(Btu / H)	18.000	24.000	36.000	48.000	60.000	
	W	5.000	7.000	10.000	14.000	16.000	
Capacidad Calefacción	(Btu / H)	20.000	27.300	37.600	53.000	61.500	
	W	5.800	8.000	11.000	15.500	18.000	
Alimentación eléctrica	V / P / Hz	220 / 1 / 50	220 / 1 / 50	380 / 3 / 50	380 / 3 / 50	380 / 3 / 50	
Power Input Enfriamiento	Kw	2,1	2,6	4	5,8	6,5	
Power Input Calefacción	Kw	1,8	2,5	3,5	5,4	5,5	
Current Input enfriamiento	A	9,3	12,1	7	10,5	11,8	
Current Input calefacción	A	8	11,4	6,3	9,8	10	
Carga de refrigerante	Kg	1,5	2	3,2	3,8	5,1	
UNIDAD INTERIOR							
Caudal de Aire	m3 / h	840	1.400	2.000	2.300	2.700	
Presión Estática Externa	Pa	60 - 40	80 - 60	150 - 100	150 - 100	150 - 100	
Nivel de Ruido	dB (A)	42	44	46	46	48	
Dimensiones de contorno (LxAxH)	cm	74 x 101 x 27	50 x 127 x 27	74x 125x 29	74x 125x 29	79x 125 x 33	
Dimensiones de empaque (LxAxH)	cm	80 x 112 x 31	60 x 135 x 27	83 x 134 x 29	83 x 134 x 29	88 x 134 x 33	
Peso Neto	Kg	36	37	57	57	66	
UNIDAD EXTERIOR							
Nivel de Ruido	dB (A)	56	59	60	63	64	
Dimensiones de contorno (LxAxH)	cm	32 x 85 x 54	41 x 102 x 70	41x 102 x 84	41x 103 x 125	41x 103 x 125	
Dimensiones de empaque (LxAxH)	cm	36 x 88 x 59	45 x 110 x 78	45 x 111 x 99	45 x 111 x 139	45 x 111 x 139	
Peso Neto	Kg	48	59	128	128	138	
TUBERIA							
Tubería de Líquido	pulgadas	1 / 4	3 / 8	1 / 2	1 / 2	1 / 2	
Tubería de Gas	pulgadas	1 / 2	5 / 8	3 / 4	3 / 4	3 / 4	
Long.Max.Tuberías	m	20	30	50	50	50	
Max.dif.entre UI y UE	m	15	15	30	30	30	

- Equipo de largo alcance
- Filtro lavable de larga duración
- Bajo nivel de ruido

